

# 1C-Metal-Coatings Brantho Korrx

easy to use – surface tolerant

> matt <

## Brantho-Korrx „nitrofest“

- ✱ for (almost) all topcoats
- ✱ primer and filler
- ✱ fast drying
- ✱ 18 colours ex works
- ✱ for iron and steel surfaces (bare or hand derusted)
- ✱ gut schleifbar

## Branth's HgS Haftgrund-Spezial

- ✱ for all metal surfaces
- ✱ even for galvanizations
- ✱ for (almost) all topcoats
- ✱ colour „grey“ ex works

## Branth's RMB „Rostschutz-Mennige, bleifrei“

- rust protection primer, mainly for manual application,
- matt, orange ex works

> semi-gloss <

## Brantho-Korrx „3 in 1“

- ✱ primer and topcoat
- ✱ 70 colours ex-works
- ✱ dirt-repellent
- ✱ elastic, adhesive
- ✱ fast dust dry
- ✱ for most topcoats
- ✱ for iron, flash rust, old coatings, aluminium, stainless steel and many more



**Brantho-Korrx „3in1“ fulfills at the same time the most demanding tests for harmlessness (toys) and corrosion protection (Norsok)**



> gloss <

## Branth's Robust-Lack

- ✱ elastic, filling, fast dust dry
- ✱ little spray-mist
- ✱ ideal with „3 in 1“
- ✱ 40 RAL- and truck-colours ex works

## Branth's S-Glasur

- ✱ top coat, smooth surface
- ✱ glow odor
- ✱ ideal on „nitrofest“
- ✱ sbrush, roller, spray application
- ✱ 36 RAL- and truck-colours ex works

## Branth's Kristall-Glasur

- clear topcoat, universal, impact-resistant, elastic, washable, weather-resistant, one-component, glossy or semi-glossy

## 2C-specials

Fast drying (from 20°C), special durabilities

### Brantho-Korrx „2-Kompo“

for iron, aluminum, stainless steel, galvanizing, primer and finish coat, semi-matt, can be painted over universally on request, white, black, light grey and lime green from stock, other colors from 30 kg in 6 kg units, for painting, rolling, spraying  
Branth's 2K-Flexi-Lack semi-matt, high-filling, hyper-flexible lacquer, extremely impact-resistant, weather-resistant, in white and black from stock, other colors from 32 kg in 4 kg units. Also available as a glossy clear topcoat from stock

### Branth's 2K-Anti-Graffiti

Air-drying, short drying time, enamel-like surface, high chemical resistance, very high gloss level, clearcoat high gloss or semi-gloss from stock, color shades from 30 kg in 5 kg units

### Branth's 2K(M-Schutzlack

glossy, crystal-clear lacquer, adheres to polished metals, wood, etc. .

### Brantho-Korrx „2K-Durasolid“

Almost solvent-free, glossy, thick-layer base and top coat for underwater use or interiors. Red-brown, black, sky blue, cream white from stock, other colors from 39 kg in 6.5 kg units

## Water-dilutable paints and varnishes...

...for metal surfaces

**Brantho-Korrx „ecobase“** matt, fast drying, for iron, aluminum, stainless steel, universally recoatable, light grey RAL 7035 from stock

### Brantho-Korrx „ecopakt“

satins gloss, for iron, aluminum, stainless steel, primer and finish coat, white RAL 9010, black RAL 9005, silveralu- RAL 9006 from stock, other colors from 30 liters minimum production quantity.

### Branth's „ecotop“

glossy, "white" from stock

...for walls, ceilings, facades

### Basak „J“

Matt coating material for walls and ceilings in all interior rooms; odorless, reduces condensation water

### Basak „WW“

Silk-gloss facade coating material, resistant to driving rain, water-repellent, water vapor permeable, weather and yellowing resistant

### Basak „Fawa“

Facade coating material with water beading effect

### Branth's Grundfestiger

water-dilutable, water vapor permeable for plaster and masonry

## Further products

### Brantho-Korrx „normal“

Natural high-solid primer and finish coat, for iron and steel, silky gloss, mild odor, high filling and covering power, for interior and exterior use, 18 shades in stock

### Edel-Firnis

impregnates wood with resin and oil; as a primer or open-pore top coat

### Rostschutzgrund

simple and effective; brown-grey, in 27.5 kg hobbcks

### Alu-Glasur (600°C)

weatherproof, heat-resistant, proven for chimney stones, pipes, tanks

### Quick-Härter

for S-Glasur or Robust Lack, faster drying (from 20°C)

### „3in1“-Härter

Faster drying, less sensitive surface

### Slide-Stopp-Additiv

750ml anti-slip granules for 5 liters of paint,color neutral

### „Spardeckel“ with pouring spout, „Spardeckel“ with dust cap

special lids for our 5 liter cans.

### Set for Komfortdosen

18 pcs. various spray nozzles and handle

### Kombi Verdünnung

strong thinning effect, fast evaporation, for all solvent-based Branth paints

### Spezial Verdünnung

mild odor, slow evaporation, strong thinning effect, for all Branth paints

## Thick-layer-paint application

convenient and direct spraying from the can

**Original Brantho-Korrx from the comfort can.** Only the shape is reminiscent of a spray can, the comfort can is completely different, much better:



- ✱ Non-toxic compressed gas from renewable raw materials
- ✱ Original Brantho-Korrx
- ✱ special surface nozzle




**The new comfort cans** enable silky-gloss paint coats of over 120 microns by spraying in a cross-coat, two coats ensure real corrosion protection. Your advantage: Efficient working thanks to full coverage without runners right from the first coat.



**Convenient for you:**

- ✱ Layer thicknesses almost like withairless spraying
- ✱ No time-consuming tool or equipment cleaning
- ✱ No skin formation in used cans

**Getting significantly more than usual!** Brantho-Korrx „3in1“ from the „Komfortdose“



## Technical data in short form for comparison

	Brantho-Korrx				Top-coats	
	3in1	nitro-fest	2-Kompo	eco-base	S-Glasur	Robust-Lack
<b>Coverage</b>						
- mathematical 30 my	17,3 m²	16,6 m²	13,3 m²	13,9 m²	18,3 m²	16,8 m²
- practical	6 m²	6 m²	4 m²	5 m²	8 m²	8 m²
<b>Drying times at 20°C</b>						
- dust-dry	25 Min.	10 Min.	20 Min.	15 Min.	75 Min.	20 Min.
- touch-dry	100 Min.	60 Min.	40 Min.	40 Min.	6 Std.	100 Min.
- dried	10 Std.	14 Std.	8 Std.	16 Std.	36 Std.	10 Std.
- stackable	72 Std.	16 Std.	16 Std.	6 Std.	2 Tage	3 Tage
- 20 Min./60°C stackable	216 Std.	45 Min.	1 Std.	60 Min.	1 Tag	5 Tage
VOC-content (g/l)	<400	<420	<380	<60	<350	<420

## This is important:

Brantho-Korrx 3in1 is approved for the construction, modification, maintenance and repair of steel structures and steel components (Ü mark). Brantho-Korrx complies with DIN-EN-ISO 12944-6 for all 6 corrosivity categories with atmospheric ambient conditions (room, rural, urban, industrial, marine atmosphere, chemically contaminated outdoor atmosphere). For the 3 corrosivity categories in water and soil, we recommend Brantho-Korrx "2K-Durasolid".

## This is popular:

Brantho-Korrx "3 in 1" has proven itself in 30 years on over 10 million square meters; as a primer, intermediate and finish coating on all metals and intact old coatings



## Further information

can be found in the technical data sheets (with processing instructions), which we have available for you, or at: [www.Brantho-Korrx.de](http://www.Brantho-Korrx.de)

## Simple, universal, durable

Brantho-Korrx is very easy to process, universally applicable, offers outstanding resistance and very high environmental compatibility.

## Proven and tested in practice

Brantho-Korrx is a comprehensively tested and documented product that has also been tried and tested in practice over many years. This gives you comprehensive security.

## Your benefit

Our coatings are the guideline for developments and enhancements. We develop and produce close to the market and cost-effectively in Germany.

## This brochure

only provides an overview of our production program. We provide detailed information on each product and will be happy to advise you.

## Alle Branth-Coatings

contain as much solids and as little solvent as technically possible. The high yield saves our customers material, labor and environmental pollution.

## Since 1887

Branth paints from Hamburg have been available for commercial users; over 10,000 companies and institutions order them regularly.